

ABR[®]

PRODUCTS, INC.

Restoring, beautifying, preserving wood and stone surfaces.

Ask about our
certification seminars!



ABR-404 GRAFFITI STOP PRODUCT SPECIFICATIONS

PRODUCT NAME

**ABR-404 Polyurethane
GRAFFITI STOP**

MANUFACTURER

American Building Restoration
Products, Inc.
9720 South 60th Street
Franklin, WI 53132
U.S.A.
(414) 421-4125
1-800-346-7532 (Orders Only)
Fax (414) 421-8696
www.abrp.com

PRODUCT DESCRIPTION

Basic Use: ABR-404 Graffiti Stop is a urethane in a complex catalyst system, designed to resist UV degradation and acts as a barrier prohibiting graffiti penetration into the surface.

ABR-404 Graffiti Stop may be used on interior and exterior surfaces of painted or bare metal, masonite, wood, brick or concrete.

Deep penetrating graffiti such as inks and shoe dyes are impossible to remove from masonry and other types of surfaces. When treated with **ABR-404 Graffiti Stop**, graffiti removal and clean up is simple and easy.

Limitations: ABR-404 Graffiti Stop does not prevent graffiti from clinging to the surface. Graffiti will require the use of a remover. See ABRP, Inc., Polyshield removers for graffiti removal. **ABR-404 Graffiti Stop** will leave a gloss finish on surface. (A flattening agent may be used to reduce to a semi-gloss.)

Note: additional coats of **ABR-404 Graffiti Stop** will not bond or adhere adequately if previous coat is not first treated with a solvent conditioner, check with **ABRP, Inc.**, for details. Call for technical assistance before applying over previously sealed or treated lightweight concrete or when applying in temperatures below 40°F.

Precautions: read the entire material safety data sheet and product label for a more thorough evaluation of hazards. Fully protect all adjacent surfaces including vegetation. Beware of wind drift onto auto and pedestrian traffic.

Use only with adequate ventilation. (Concentrated vapors are considered explosive.) Spray only in OSHA approved environments, extinguish all pilot lights, flames, etc.

TECHNICAL DATA

Color/Form: clear liquid.

Coverage: 250 to 300 sq. ft. per gallon, on dense, smooth surface, less on rough, porous surfaces.

VOC content limit: 250 grams per liter (2.1 lbs. per gallon).

Packaging: one, five and fifty-five gallon containers.

INSTALLATION

Preparatory Work: surface must be free of any existing graffiti as well as any dust or other surface contaminants. If necessary, clean surface with **ABR 800 Fast Acting** graffiti remover. **ABR-404 Graffiti Stop will not adhere to wet surfaces, therefore**

the surface must be completely dry before application.

A test area should be performed prior to beginning overall project to determine precise procedures necessary for most effective results and compatibility to surface being treated. User shall determine the suitability of the product for its intended use and assumes all risk and liability whatsoever in connection therewith.

Application:

1. Apply with a brush or airless paint sprayer.
2. **A minimum of 2 coats** must be applied for adequate protection. Allow first coat to dry 20 minutes then reapply second coat.
3. Once surface has been fully protected, future graffiti can be easily removed with **Super Bio Strip™**, an easy and safe method.

AVAILABILITY

Available through a network of distributors, dealers and representatives established in principal cities across the United States, Canada and Japan.

NOTICE: the information and recommendations made herein are based on **ABRP, Inc.**, research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because **ABRP, Inc.**, cannot anticipate every possible application of **ABRP, Inc.**, products, nor anticipate every variation encountered in project surfaces, job conditions, and methods used. For this

reason, purchasers shall make their own tests to determine the suitability of such products for a particular purpose. Purchasers assume all risk of use, application and handling of products. Statements concerning the possible use of **ABRP, Inc.**, products are not intended as recommendation to use **ABRP, Inc.**, products in the infringement of any patent.

LIMITED WARRANTY

This warranty is valid for one year from the date of purchase. The purchaser of this product shall be entitled to the following, if the product herein is shown to be defective: **ABRP, Inc.**, at its option, will either replace the product or refund the purchase price. Contact **ABRP, Inc.**, to make claim under this warranty. The purchaser must have proof of purchase from label and original sales receipt. Proper surface preparation is essential to the applicability of this warranty. Read and follow label directions.

ABRP, Inc., shall not be liable for incidental, consequential or indirect damage arising from the use of this product or the cost of labor involved in its application.

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

No other warranties are made, expressed or implied, including without limitation warranties as to MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

This limited warranty may not be modified or extended by manufacturer's representatives, distributors or dealers of **ABRP, Inc.**, products.

Some states do not allow the exclusion or limitation of incidental or consequential damages so the above limitation or exclusion may not apply

to the purchaser. This warranty gives the purchaser specific legal rights, as well as, other rights which may vary from state to state.

TECHNICAL SERVICES

ABRP, Inc., employs in field technical representatives to answer questions for architects, building owners and contractors.

REFERENCING

Catalog, product specifications, brochures, list of national registered historical landmarks restored with **ABRP, Inc.**, products and video training tapes are available upon specific request.

ABRP, INC., is on the **WORLD WIDE WEB**. For more information on many of the specialty building restoration products available to you, please see our home page at <http://www.abrp.com> or e-mail **ABRP, Inc.** at abrp@execpc.com.

©Copyright, 2000, American Building Restoration Products, Inc.