

Grout Sealer

Interior

DESCRIPTION: Safecoat Grout Sealer is a clear, moisture resistant sealer for porous tile grout and other cementitious surfaces. It actually reacts with and becomes a part of the grout, increasing water resistance and minimizing the penetration of liquids, helping to prevent staining and giving a wearable, washable surface. Like all Safecoat products, it is as safe and not toxic as possible, formaldehyde free and virtually odorless, giving off no offensive chemical fumes. Dries clear without discoloration.

USE ON: Unsealed tile grout. May also be effective on a variety of other porous cementitious surfaces (test first). For previously sealed grout, conduct several small test patches for absorption and compatibility.

PRODUCT NUMBER AND CONTAINER SIZE:

31203 (quart).

ADVANTAGES / SIGNIFICANT BENEFITS:

- Good water resistance for up to five years when properly applied.
- Low odor, non-offensive to installer and occupant.
- Safely used by and for the chemically sensitive.
- Fights indoor air pollution, seals in the outgassing from the substrate.
- Zero VOC content, meets or exceeds all federal and state air quality regulations, including California.
- Contains no formaldehyde.

SURFACE PREPARATION: Grout must be clean, dry, free from dirt, dust, efflorescence, grease, wax, oil, silicone, tsp/soap, mill scale, oxidation, loose peeling paint or varnish, or any foreign matter/contaminants. Remove all mildew before coating any surface. It should not be necessary to apply a release compound to tiles before sealing, but note application instructions carefully.

COVERAGE: Variable depending on method of application and surface porosity. Generally one quart will cover a minimum of 100 feet of standard grout lines. Do not thin.

APPLICATION: Always have adequate ventilation. Apply to grout liberally and in an even manner, using a sponge, dry lint-free rag, small brush, or any other tool which can be used comfortably. Flood coating is acceptable, but avoid puddling. One coat is generally sufficient. **IMPORTANT:** Wipe off any sealer which has not penetrated into the grout within 10-15 minutes; do not allow sealer which has not soaked in to dry on the surface (simply wipe off with a

slightly damp cloth or sponge). Always test a sample for suitability prior to full use.

CLEAN-UP: Clean tools and equipment while they are still wet with a solution of **SafeChoice Super Clean** and warm water.

DRYING/CURING TIME: Under normal conditions, Safecoat Grout Sealer dries to the touch within one hour and cures within 24 hours. Normal conditions include a clean, dry surface, access to fresh air flow, a dust free environment, moderate humidity, and temperatures above 55 degrees F. Thick application, high humidity or conditions other than normal will cause Safecoat Grout Sealer to dry and cure more slowly. Avoid using sealed surface for at least 24 hours after application.

LIMITATIONS: Safecoat Grout Sealer is made without formaldehyde preservatives. Do not contaminate. Store in airtight containers. Do not use when ambient or surface temperature is below 55°F.

HEALTH PRECAUTIONS: As with all coatings and sealers, keep container tightly closed and out of the reach of children. Do not take internally. Keep from freezing. Always use adequate ventilation. If you are chemically sensitive, always test for personal tolerance.

LIMITED LIABILITY: The great variation between environmental factors, possible surfaces and application techniques, and the lack of control we have over such matters, must affect our policies. Safecoat products are guaranteed not to be defective when applied and used in accordance with instructions. However, liability, whether express or implied, is limited to replacement of product or refund of purchase price and cannot include liability for labor costs or consequential damages. Because of the variety of circumstances affecting each job, it is the user's responsibility to determine the suitability and safety of the product for any particular application. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of AFM products. **We particularly recommend that users always test in small inconspicuous areas before application to the entire surface.**